



ALCOSAN VT10

Revision: 2020-08-11

Version: 02.0

SECTION 1: Identification of the substance/mixture and supplier

1.1 Product identifier

Product name: ALCOSAN VT10

1.2 Recommended use and restrictions on use

Identified uses:

Hard surface sanitiser

Restrictions of use:

Uses other than those identified are not recommended

1.3 Details of the supplier

Diversey Australia Pty. Limited

29 Chifley St, Smithfield, NSW, 2164, Australia

Telephone: 1800 647 779 (toll free)

Fax: (02) 9725 5767

Email: aucustserv@diversey.com

Website: www.diversey.com/

1.4 Emergency telephone number

Seek medical advice (show the label or safety data sheet where possible)

Call 1800 033 111 (24hrs)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Flammable liquids, Category 3

Specific target organ toxicity (single exposure), Category 3

Serious eye irritation, Category 2

2.2 Label elements



Signal word: Warning

Hazard statements:

H226 - Flammable liquid and vapour.

H336 - May cause drowsiness or dizziness.

H319 - Causes serious eye irritation.

Prevention statement(s):

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 - Keep container tightly closed.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical, ventilating or lighting equipment.

P242 - Use non-sparking tools.

P243 - Take action to prevent static discharges.

P261 - Avoid breathing vapours.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing and eye or face protection.

Response statement(s):

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

ALCOSAN VT10

Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice or attention.

P312 - Call a POISON CENTRE, doctor or physician if you feel unwell.

P363 - Wash contaminated clothing before reuse.

Storage statement(s):

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

Disposal statement(s):

P501 - Dispose of unused content as chemical waste.

2.3 Other hazards

No other hazards known.

SECTION 3: Composition/information on ingredients**3.1 Substances / Mixtures**

Ingredient(s)	CAS number	EC number	Weight percent
propan-2-ol	67-63-0	200-661-7	10-30

Non-hazardous ingredients are the remainder and add up to 100%.

Workplace exposure limit(s), if available, are listed in subsection 8.1.

SECTION 4: First aid measures**4.1 Description of first aid measures****Inhalation:**

Remove person to fresh air and keep comfortable for breathing.

Skin contact:

Take off immediately all contaminated clothing and wash it before reuse.

Eye contact:

Hold eyelids apart and flush eyes with plenty of lukewarm water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation occurs and persists, get medical attention.

Ingestion:

Rinse mouth. Immediately drink 1 glass of water. Never give anything by mouth to an unconscious person. Get medical attention or advice if you feel unwell.

Self-protection of first aider:

Consider personal protective equipment as indicated in subsection 8.2.

First aid facilities:

Eyewash facilities should be considered in a workplace where necessary.

4.2 Most important symptoms and effects, both acute and delayed**Inhalation:**

May cause drowsiness or dizziness.

Skin contact:

No known effects or symptoms in normal use.

Eye contact:

Causes severe irritation.

Ingestion:

No known effects or symptoms in normal use.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

Poison Information Center:

Call 13 11 26 (Australia Wide).

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Carbon dioxide. Dry powder. Water spray jet. Fight larger fires with water spray jet or alcohol-resistant foam.

5.2 Special hazards arising from the substance or mixture

No special hazards known.

5.3 Advice for firefighters

As in any fire, wear self contained breathing apparatus and suitable protective clothing including gloves and eye/face protection.

5.4 Hazchem code

None allocated

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Turn off all sources of ignition. Ventilate the area. Ensure adequate ventilation. Do not breathe dust or vapour. Wear suitable protective

ALCOSAN VT10

clothing, gloves and eye/face protection.

6.2 Environmental precautions

Do not allow to enter drainage system, surface or ground water. Dilute with plenty of water.

6.3 Methods and material for containment and cleaning up

Ensure adequate ventilation. Dyke to collect large liquid spills. Absorb with liquid-binding material (sand, diatomite, universal binders, sawdust). Do not place spilled materials back into the original container. Collect in closed and suitable containers for disposal.

6.4 Reference to other sections

For personal protective equipment see subsection 8.2. For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Measures to prevent fire and explosions:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools.

Measures required to protect the environment:

For environmental exposure controls see subsection 8.2.

Advices on general occupational hygiene:

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Handle and open container with care. Do not mix with other products unless advised by Diversey. Wash hands before breaks and at the end of workday. Take off immediately all contaminated clothing. Store used personal protective equipment separately. Avoid contact with skin and eyes. Do not breathe vapours. Use only with adequate ventilation. See chapter 8.2, Exposure controls / Personal protection.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local and national regulations. Store in a well-ventilated place. Store in a closed container. Keep only in original packaging. Keep from freezing. Keep cool. Keep away from heat and direct sunlight.

For conditions to avoid see subsection 10.4. For incompatible materials see subsection 10.5.

7.3 Specific end use(s)

No specific advice for end use available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits

Air limit values, if available:

Ingredient(s)	Long term value(s) (TWA)	Short term value(s) (STEL)	Peak value(s)
propan-2-ol	400 ppm 983 mg/m ³	500 ppm 1230 mg/m ³	

Biological limit values, if available:

8.2 Exposure controls

The following information applies for the uses indicated in subsection 1.2 of the Safety Data Sheet.

If available, please refer to the product information sheet for application and handling instructions.

Normal use conditions are assumed for this section.

Recommended safety measures for handling the undiluted product:

Appropriate engineering controls: No special requirements under normal use conditions.
Appropriate organisational controls: Avoid direct contact and/or splashes where possible. Train personnel.

Personal protective equipment

Eye / face protection:

Safety glasses or goggles (EN 166).

Hand protection:

Chemical-resistant protective gloves (EN 374). Verify instructions regarding permeability and breakthrough time, as provided by the gloves supplier. Consider specific local use conditions, such as risk of splashes, cuts, contact time and temperature.

Suggested gloves for prolonged contact: Material: butyl rubber Penetration time: ≥ 480 min Material thickness: ≥ 0.7 mm

Suggested gloves for protection against splashes: Material: nitrile rubber Penetration time: ≥ 30 min Material thickness: ≥ 0.4 mm

In consultation with the supplier of protective gloves a different type providing similar protection may be chosen.

Body protection:

Wear chemical-resistant clothing and boots in case direct dermal exposure and/or splashes may occur (EN 14605).

ALCOSAN VT10

Respiratory protection:	Respiratory protection is not normally required. However, inhalation of vapour, spray, gas or aerosols should be avoided.
Environmental exposure controls:	Should not reach sewage water or drainage ditch undiluted or unneutralised.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

	Method / remark
Physical State: Liquid	
Colour: Clear, Colourless	
Odour: Product specific	
Odour threshold: Not applicable	
pH ≈ 5.1 (neat)	ISO 4316
Dilution pH: ≈ 5.5 (10%)	
Melting point/freezing point (°C): Not determined	Not relevant to classification of this product
Initial boiling point and boiling range (°C): Not determined	
Flammability (liquid): Flammable.	
Flash point (°C): ≈ 25 °C	closed cup
Sustained combustion: The product sustains combustion (<i>UN Manual of Tests and Criteria, section 32, L.2</i>)	UN Manual of Tests and Criteria, section 32, L.2
Evaporation rate: Not determined	Not relevant to classification of this product
Flammability (solid, gas): Not applicable to liquids	
Upper/lower flammability limit (%): Not determined	
Vapour pressure: Not determined	
Vapour density: Not determined	Not relevant to classification of this product
Relative density: ≈ 0.96 (20 °C)	OECD 109 (EU A.3)
Solubility in / Miscibility with Water: Fully miscible	
Partition coefficient: n-octanol/water No information available.	

Substance data, partition coefficient n-octanol/water (log Kow): see subsection 12.3

Autoignition temperature: Not determined
Decomposition temperature: Not applicable.
Viscosity: Not determined
Explosive properties: Not explosive. Vapours may form explosive mixtures with air.
Oxidising properties: Not oxidising

9.2 Other information

Surface tension (N/m): Not determined	
Corrosion to metals: Not corrosive	Weight of evidence

SECTION 10: Stability and reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal storage and use conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known under normal storage and use conditions.

10.4 Conditions to avoid

Take action to prevent static discharges.

10.5 Incompatible materials

None known under normal use conditions.

10.6 Hazardous decomposition products

None known under normal storage and use conditions.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Mixture data:.

Relevant calculated ATE(s):

ATE - Oral (mg/kg): >2000

Substance data, where relevant and available, are listed below:.

Acute toxicity

Acute oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
propan-2-ol	LD ₅₀	3570	Rat	Method not given	

Acute dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg)	Species	Method	Exposure time (h)
propan-2-ol	LD ₅₀	> 2000	Rabbit	Method not given	

Acute inhalative toxicity

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	LC ₅₀	> 25 (vapour)	Rat	OECD 403 (EU B.2)	6

Irritation and corrosivity

Skin irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	Not irritant	Rabbit	OECD 404 (EU B.4)	

Eye irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	Irritant	Rabbit	OECD 405 (EU B.5)	

Respiratory tract irritation and corrosivity

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	No data available			

Sensitisation

Sensitisation by skin contact

Ingredient(s)	Result	Species	Method	Exposure time (h)
propan-2-ol	Not sensitising	Guinea pig	OECD 406 (EU B.6) / Buehler test	

Sensitisation by inhalation

Ingredient(s)	Result	Species	Method	Exposure time
propan-2-ol	No data available			

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Mutagenicity

Ingredient(s)	Result (in-vitro)	Method (in-vitro)	Result (in-vivo)	Method (in-vivo)
propan-2-ol	No evidence for mutagenicity, negative test results No evidence of genotoxicity, negative test results	OECD 471 (EU B.12/13)	No evidence of genotoxicity, negative test results	OECD 474 (EU B.12)

Carcinogenicity

Ingredient(s)	Effect
propan-2-ol	No evidence for carcinogenicity, negative test results

Toxicity for reproduction

Ingredient(s)	Endpoint	Specific effect	Value (mg/kg bw/d)	Species	Method	Exposure time	Remarks and other effects reported
propan-2-ol			No data available				

Repeated dose toxicity

Sub-acute or sub-chronic oral toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected

ALCOSAN VT10

propan-2-ol		No data available				
-------------	--	-------------------	--	--	--	--

Sub-chronic dermal toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
propan-2-ol		No data available				

Sub-chronic inhalation toxicity

Ingredient(s)	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time (days)	Specific effects and organs affected
propan-2-ol		No data available				

Chronic toxicity

Ingredient(s)	Exposure route	Endpoint	Value (mg/kg bw/d)	Species	Method	Exposure time	Specific effects and organs affected	Remark
propan-2-ol			No data available					

STOT-single exposure

Ingredient(s)	Affected organ(s)
propan-2-ol	Central nervous system

STOT-repeated exposure

Ingredient(s)	Affected organ(s)
propan-2-ol	Central nervous system

Aspiration hazard

Substances with an aspiration hazard (H304), if any, are listed in section 3.

Potential adverse health effects and symptoms

Effects and symptoms related to the product, if any, are listed in subsection 4.2.

SECTION 12: Ecological information**12.1 Toxicity**

No data is available on the mixture.

Substance data, where relevant and available, are listed below:

Aquatic short-term toxicity

Aquatic short-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	LC ₅₀	> 100	<i>Pimephales promelas</i>	Method not given	48

Aquatic short-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	EC ₅₀	> 100	<i>Daphnia magna Straus</i>	Method not given	48

Aquatic short-term toxicity - algae

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (h)
propan-2-ol	EC ₅₀	> 100	<i>Scenedesmus quadricauda</i>	Method not given	72

Aquatic short-term toxicity - marine species

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time (days)
propan-2-ol		No data available			-

Impact on sewage plants - toxicity to bacteria

Ingredient(s)	Endpoint	Value (mg/l)	Inoculum	Method	Exposure time

ALCOSAN VT10

propan-2-ol	EC ₅₀	> 1000	Activated sludge	Method not given	
-------------	------------------	--------	---------------------	------------------	--

Aquatic long-term toxicity

Aquatic long-term toxicity - fish

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
propan-2-ol		No data available				

Aquatic long-term toxicity - crustacea

Ingredient(s)	Endpoint	Value (mg/l)	Species	Method	Exposure time	Effects observed
propan-2-ol		No data available				

Aquatic toxicity to other aquatic benthic organisms, including sediment-dwelling organisms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw sediment)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity

Terrestrial toxicity - soil invertebrates, including earthworms, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - plants, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - birds, if available:

Ingredient(s)	Endpoint	Value	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - beneficial insects, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

Terrestrial toxicity - soil bacteria, if available:

Ingredient(s)	Endpoint	Value (mg/kg dw soil)	Species	Method	Exposure time (days)	Effects observed
propan-2-ol		No data available			-	

12.2 Persistence and degradability**Abiotic degradation**

Abiotic degradation - photodegradation in air, if available:

Abiotic degradation - hydrolysis, if available:

Abiotic degradation - other processes, if available:

Biodegradation

Ready biodegradability - aerobic conditions

Ingredient(s)	Inoculum	Analytical method	DT ₅₀	Method	Evaluation
propan-2-ol			95 % in 21 day(s)	OECD 301E	Readily biodegradable

ALCOSAN VT10

Ready biodegradability - anaerobic and marine conditions, if available:

Degradation in relevant environmental compartments, if available:

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log Kow)

Ingredient(s)	Value	Method	Evaluation	Remark
propan-2-ol	0.05	OECD 107	No bioaccumulation expected	

Bioconcentration factor (BCF)

Ingredient(s)	Value	Species	Method	Evaluation	Remark
propan-2-ol	No data available				

12.4 Mobility in soil

Adsorption/Desorption to soil or sediment

Ingredient(s)	Adsorption coefficient Log Koc	Desorption coefficient Log Koc(des)	Method	Soil/sediment type	Evaluation
propan-2-ol	No data available				Potential for mobility in soil, soluble in water

12.5 Other adverse effects

No other adverse effects known.

SECTION 13: Disposal considerations**13.1 Waste treatment methods**

Waste from residues / unused products:

The concentrated contents or contaminated packaging should be disposed of by a certified handler or according to the site permit. Release of waste to sewers is discouraged. The cleaned packaging material is suitable for energy recovery or recycling in line with local legislation.

Empty packaging

Recommendation:

Dispose of observing national or local regulations.

Suitable cleaning agents:

Water, if necessary with cleaning agent.

SECTION 14: Transport information**ADG, IMO/IMDG, ICAO/IATA**

14.1 UN number: 1987

14.2 UN proper shipping name:

Alcohols, n.o.s. (isopropanol)

14.3 Transport hazard class(es):

Transport hazard class (and subsidiary risks): 3

14.4 Packing group: III

14.5 Environmental hazards:

Environmentally hazardous: No

Marine pollutant: No

14.6 Special precautions for user: None known.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code: The product is not transported in bulk tankers.

Other relevant information:

Hazchem code: None allocated

ADR

EmS: F-E, S-D

The product has been classified, labelled and packaged in accordance with the requirements of ADG7.6 Code and the provisions of the IMDG Code.

Transport regulations include special provisions for certain classes of dangerous goods packed in limited quantities.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Globally Harmonised System of Classification and Labelling of Chemicals (GHS) as published by Safework Australia.
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classification	Globally Harmonised System of Classification and Labelling of Chemicals (GHS) as published by Safework Australia.
Inventory listing(s)	Australian Inventory of Industrial Chemicals: All components are listed on the inventory, or are exempt.

SECTION 16: Other information

The information in this document is based on our best present knowledge. However, it does not constitute a guarantee for any specific product features and does not establish a legally binding contract

SDS code: MS31001037

Version: 02.0

Revision: 2020-08-11

Additional information:

Respirators: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

Work practices - solvents: Organic solvents may present both a health and flammability hazard. It is recommended that engineering controls should be adopted to reduce exposure where practicable (for example, if using indoors, ensure explosion proof extraction ventilation is available). Flammable or combustible liquids with explosive limits have the potential for ignition from static discharge. Refer to AS 1020 (The control of undesirable static electricity) and AS 1940 (The storage and handling of flammable and combustible liquids) for control procedures.

Exposure standards - Time Weighted Average (TWA) or Workplace Exposure Standard (WES) (NZ): Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

Personal protective equipment guidelines: The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health effects from exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Safety Data Sheet which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations and acronyms:

- DNEL - Derived No Effect Limit
- AUH - Non GHS hazard statement
- PNEC - Predicted No Effect Concentration
- ATE - Acute Toxicity Estimate
- LD50 - Lethal Dose, 50% / Median Lethal dose
- LC50 - Lethal Concentration, 50% / Median Lethal Concentration
- EC50 - effective concentration, 50%
- NOEL - No observed effect level
- NOAEL - No observed adverse effect level
- STOT-RE - Specific target organ toxicity (repeated exposure)
- STOT-SE - Specific target organ toxicity (single exposure)
- EC No. - European Community Number
- OECD - Organization for Economic Cooperation and Development

End of Safety Data Sheet